



Alabama State Port Authority

Specification Booklet

Project Name McDuffie Parking Lot Expansion

Project No. 11515 **Task No.** 01 **Addendum No.** 3

To: Prospective Bidders

Date: 12/17/2025

The following items are clarifications and revisions.

| Item | Description |
|---------------------------------------|---|
| Clarifications & Revisions | |
| 1. | Pay Item #11 is revised to "6 inches ALDOT Section 230 Modified Roadbed Processing Compacted to 100% Standard Proctor Density". Improved roadbed processing is not expected to be required with this project. |
| 2. | The plan quantity for Pay Item #10 "Borrow Excavation (A-2-4(0) Or A-4(0))" is increased to 600 CYIP. |
| 3. | Revised Division I: Page 4 (attached) – Revised to reflect the revisions listed above. Replace previous Division I Page 4 and include the attached Division I Page 4 with the bid. |

Please indicate your receipt of this addendum by adding the addendum number in the appropriate place in your Specification Book.

Project Manager:

A handwritten signature in blue ink that appears to read 'Kyle Strachan'.

12/17/2025

Kyle Strachan, P.E.



Project Name McDuffie Parking Lot Expansion **Specification Booklet**

Location Mobile, AL

Project # 11515 **TASK#** 1 **November 2025**

4 | Page

McDuffie Warehouse Parking Lot Expansion

Base Bid

| Item No. | ALDOT Pay Item | Description | Qty | Units | Unit Price | Total |
|-----------------|-----------------------|--|------------|--------------|-------------------|--------------|
| 1.0 | | Project Bonds & Insurance | 1 | LS | | |
| 2.0 | | Mobilization | 1 | LS | | |
| 3.0 | | Demobilization | 1 | LS | | |
| 4.0 | 206D-011 | Remove Existing Fence | 85 | LF | | |
| 5.0 | 634B-002 | Install New Perimeter Fence, 8ft Tall with Barbed Wire | 830 | LF | | |
| 6.0 | | Install Temporary Fence | 950 | LF | | |
| 7.0 | 206E-000 | Removing Headwalls | 1 | EA | | |
| 8.0 | | Relocate Rock to Location Directed by Alabama Port Authority | 300 | SQ YD | | |
| 9.0 | 210A-000 | Unclassified Excavation | 1500 | CYIP | | |
| 10.0 | 210D-012 | Borrow Excavation (A-2-4(0) Or A-4(0)) | 600 | CYIP | | |
| 11.0 | 230 | 6" ALDOT Section 230 Modified Roadbed Compacted to 100% Standard Proctor Density | 3940 | SQ YD | | |
| 12.0 | 301A-012 | Crushed Aggregate Base Course, Type B. Plant Mixed 6" Compacted Thickness | 3900 | SQ YD | | |
| 13.0 | 424A-341 | Superpave Bituminous Concrete Wearing Surface Layer, 3/4" Maximum Aggregate Size Mix, ESAL Range A/B | 450 | TON | | |
| 14.0 | 530A-001 | 18" Roadway Pipe (Class 3 R.C) - includes tying into existing inlets | 40 | LF | | |
| 15.0 | 530B-000 | 18" Span, 11" Rise Roadway Pipe (Class 3 R.C.) - includes concrete collar | 48 | LF | | |
| 16.0 | | 18" Span, 11" Rise Concrete 4:1 Slope Paved Headwall (Double Line) | 1 | EA | | |
| 17.0 | | 8" Thick Concrete Sidewalk Adjacent to Asphalt | 460 | LF | | |
| 18.0 | | Concrete Parking Bumpers | 53 | EA | | |
| 19.0 | 618A-000 | 4" Thick Concrete Sidewalk (3000 psi Mix) | 265 | SQ YD | | |
| 20.0 | 618B-003 | Concrete Pavement, 6" Thick (Includes Wire Mesh) 4000 psi Mix | 144 | SQ YD | | |
| 21.0 | | Install New Inlet Structure w/ Relocated Grate (Structure "A") | 1 | EA | | |
| 22.0 | | Modify Inlet w/ Manhole Frame & Cover (Structures "B" & "D") | 2 | EA | | |
| 23.0 | | Install New Inlet & Box (Structure "C") | 1 | EA | | |
| 24.0 | 650A-000 | Topsoil | 125 | CUYD | | |
| 25.0 | 654A-000 | Solid Sodding | 1100 | SQ YD | | |